

SPREADER - 14" ELECTRIC 1/3 - 1 YARD

Commercial grade quality,
for business or personal
use

Low profile, 26" height,
for better rearward
visibility, in smaller
trucks.



Stainless steel
motor casing.

Same 14" conveyor
features & 662 Pintle
chain as its larger, gas
power counterparts

0604E shown w/
standard 6" chute

SPECIFICATIONS

	(Baby)	(Gator)	(JR.)			
Model #	0302E	0304E	0604E	1006E	1207E	1408E
Capacity: (yards)	0.3	0.3	0.6	1.0	1.2	1.4
Hopper size: (LxWxH)	24" x 50" x 26"	48" x 35" x 18"	48" x 50" x 26"	72" x 50" x 26"	84" x 50" x 26"	96" x 50" x 26"
Hopper construction: (SS)	16GA			14GA		
Conveyor Rail: (SS)	12GA			14GA		
Conveyor bed: (SS)	12GA					
Top screens: (3" openings)	n/a	Optional	Optional	2	2	2
Side gussets: (per side)	n/a	n/a	n/a	2	2	2
Ship weight: lbs. (est. . avg.)	250	310	340	650	760	870
Loaded weight: (2900# per yard) 90/10% sand/salt mix. lbs.	1120	1180	2080	3550	4240	4930
Loaded weight: (1460# per yard) 100% coarse salt lbs.	688	748	1216	2110	2512	2914

STANDARD FEATURES

- * 1/2 HP Electric, Stainless motor
- * 50:1 gearbox reduction @ conveyor
- * Enclosed motor platform w/ rear venting
- * 1 1/8" diameter conveyor shafts w/ 6T cast sprockets
- * 662 Pintle chain w/ 8500# tensile strength
- * Greasable, self aligning, drive bearings throughout
- * Recessed lifting hook & 4 corner tie down points
- * Third brake light, rubber mounted.
- * Inverted - V deflector on 7' & 8' models
- * Adjustable feed gate w/ salt flap.
- * Formed over rail w/ built in chain shields
- * Enclosed chute w/ 2 internal, adjustable baffles & 3 external, adjustable spreading deflectors, w/ spring loaded locking rods

OPTIONS

- * **DUAL** electric drive motors
(w/ variable speed control, for spinner only)
- * Extended chute
- * Flip chute (N/A for dual electric)
- * Receiver hitch mount (0302E only)
- * Vibrator, 200#
- * Polypropylene spinner disc
- * Hydraulic direct drive
- * Strobe light, (in lieu of brake light)

DO NOT EXCEED VEHICLE GVWR

Distributed by:



DownEaster ❄️

120 Old Lisbon RD. - Topsham, ME 04086

(207) 729-5101 - Fax (207) 729-8782

www.downeastermfg.com



Specifications subject to change without notice