

DUMP TRAILER - TRC612LP - CONTRACTOR SERIES



SPECIFICATIONS

\$		\$
----	--	----

Model#	TRC612L6	TRC612L6-DE
GVWR: #	12,000 lbs.	12,000 lbs.
Curb weight: (standard gate)	2,860 lbs.	2,975 lbs.
Payload capacity:	9,140 lbs.	8,980 lbs.
Volume: (level)	5.16 cubic yards	(10 yards) 288 cubic ft.
Bed size width x length:	72" x 143.5"	
Deck height:	28"	
Side plate height:	48"	
Tire size:	235/80R16 E (radial)	
Axle capacity: (2)	6000 lbs.	
Cylinder bore x length:	3.5" x 34"	



Optional Barn door, full height, extensions

STANDARD FEATURES

- * 12 gauge floor / 14 gauge side plates
- * 5" tube main frame
- * 5" channel tongue frame
- * Barn doors, 21" high
- * EZ Lube Dexter axle(s)
- * 10' pendant control cord
- * Lockable pump/battery box
- * LED rubber mounted lighting
- * 7-way RV plug w/ charge circuit
- * 16K safety chain rating (each)
- * 8K Top wind drop leg jack
- * 2 5/16" adjustable coupler
- * Tread plate fenders
- * **DuPont™ Imron® Elite black oven cured paint w/ epoxy primer**
- * Two Year Limited Warranty
- * Dual acting pump

OPTIONS

- * Mesh roller tarp, manual
- * Barn Door full height extension kit
- * Spare tire mount w/ wheel & tire
- * Battery tender (weatherproof)
- * 12-volt deep cycle battery
- * D-rings 3/8" diameter, bolt on (for general purpose)
- * 12K Top wind drop leg jack (12')
- * Pintle ring, 7 ton



Adjustable Coupler & 8K Drop Leg jack, standard.

No color options available for this model

Distributed by:

DownEaster

120 Old Lisbon RD. - Topsham, ME 04086

(207) 729-5101 - Fax (207) 729-8782

www.downeastermfg.com

