

SPREADER - 24" HYDRAULIC 5 - 15 YARD



Screen hinges



Remote grease fittings, standard



6:1 spur gear



Standard adjustable chute shown

SPECIFICATIONS

All units 83.5" wide,
12GA SS / 10GA HR hopper
construction & 45 deg.
sloped sides

Height	Hopper length							
	9'	10'	11'	12'	13'	14'	15'	16'
48"	5.1	5.6	6.2	6.8	7.3	7.9	8.4	9.2
54"	6.2	7.0	7.6	8.4	9.0	9.7	10.3	11.2
60"	7.4	8.3	9.0	9.9	10.7	11.6	12.2	13.2
66"	8.6	9.5	10.3	11.5	12.3	13.5	14.2	15.2
Capacity (cubic yards)								

Ship weight: (lbs) (median)	2250	2410	2560	2710	2870	3020	3170	3350
Loaded weight: (2900# per yard) 90/10% sand/salt mix lbs (lowest to highest yardage)	17040	18650	20540	22430	24040	25930	27530	30030
	27190	29960	32430	36060	38540	42170	44350	47430
Loaded weight: (1460# per yard) 100% coarse salt lbs. (lowest to highest yardage)	9696	10586	11612	12638	13528	14554	15434	16782
	14806	16280	17598	19500	20828	22730	23902	25542

STANDARD FEATURES

- * Stainless steel conveyor bed
- * Rear conveyor take up adjustment
- * Remote rear grease fittings
- * Double bend top rail, all around
- * Formed over rail w/ built in chain shields
- * 2" diameter drive shaft w/ 6T cast sprockets
- * 667 Pintle chain w/ 9500# tensile strength
- * Greasable, self aligning, drive bearings throughout
- * Adjustable feed gate, via screw jack
- * 4 corner tie down points
- * Enclosed chute w/ internal adjustable baffle
& 3 external adjustable spreading deflectors
- * 6:1 spur gear

- * Vertical gussets every 24"
- * Hinged & sloped removable top screens

OPTIONS

- * Flip chute - manual or electric winch
- * Inverted - V deflector
- * Stainless steel spinner disc w/ replaceable vanes
- * Doghouse front endplate, for telescopic dump bodies
- * 50:1 worm gear drive
- * Spill shields, front or rear, 45 deg. sloped
- * Cat walks, both sides

DO NOT EXCEED VEHICLE GVWR

Distributed by:



Specifications subject to change without notice