SPREADER - 14" GAS / ELECTRIC 3 - 8 YARD

Double bend construction all around & on gussets

Bolt on 7" hopper extension, for 1 yard increased hopper capacity

24 Group, battery box

Reliable Briggs & Stratton or Honda gas drive

Quick adjust deflectors

*Shown w/ optional wireless remote

SPECIFICATIONS

All units 71" wide

Model #	3108	3509	3810	4008	4509	5010	6010 ₁	8012 ₂
Yard Capacity Level:	**3.1**	**3.5**	**3.8**	**4.0**	**4.5**	**5.0**	**6.0**	**8.0**
Yard Capacity rounded:	*3.5*	*3.9*	*4.3*	*4.5*	*5.1*	*5.6*	*6.5*	*8.6*
Hopper Length:	8'	9'	10'	8'	9'	10'	10'	12'
Hopper Height: (@ center)	47"			54" (7" hopper extension)			59"	65"
Ship weight: lbs (est. . avg.)	1000	1050	1110	1020	1080	1150	1230	1540
Loaded weight: *(2900# per yard)* 90/10% sand/salt mix lbs	*9990*	*11200*	*12217*	*12620*	*14130*	*15650*	*18630*	*24740*
Loaded weight: *(1460# per yard)* 100% coarse salt lbs.	5526	6160	6702	6860	7650	8450	9990	13220

(ship weight based on gas engine drive & standard chute)

STANDARD FEATURES

* 14GA 304 SS hopper construction
* 12GA 304 SS conveyor bed
* 3 vertical gussets per side
* Bolt together hopper extensions
* Hinged / removable tapered top screens
* 45 deg. Sloped sides
* Double bend top rail, all around
* Formed over rail w/ built in chain shields
* 1 1/8" diameter conveyor shafts w/ 6T cast sprockets
* 662 Pintle chain w/ 8500# tensile strength
* Greasable, self aligning, drive bearings throughout
* Adjustable feed gate w/ salt flap.
* 4 corner tie down points
* Enclosed chute w/ 2 internal, & 3 external, adjustable spreading spring loaded locking rods

DRIVE OPTIONS

* Briggs & Stratton 10.5 HP
* Honda 11 HP
* Honda 5.5 HP, self contained gas over hydraulic
* Direct, hydraulic drive *(requires host vehicle power)*
* 3/4 HP Electric single drive motor, thru 20:1 reduction gearbox
* **DUAL** electric drive motors *(w/ variable speed control, for spinner only)*
* **Premium DUAL** electric drive motors *(w/ variable speed control, for both motors)*

OPTIONS

* Wireless remote control *(gas only)*
* Extended chute (12")
* 24 group marine battery
* Inverted - V deflector *(std on electric & 8.0 yard)*
* Flip chute *(N/A for dual electric)*
* Polypropylene spinner disc

NOTES

1. welded hopper, extensions N/A
2. 5 gussets per side, 10' conveyor

Distributed by:

DownEaster
WWW.DOWNEASTERMFG.COM

NTEA
THE ASSOCIATION FOR THE WORK TRUCK INDUSTRY

Specifications subject to change without notice

Rev D