

# **DownEaster**

**BUILT TOUGH, BUILT TO LAST**

**Since 1979**

# **DROP SIDE DUMP BODY**



2017 GM 60" CA 3500 shown

## **Designed with the features you expect.**

Reliable and rugged scissor hoist, for proven load dumping of the heaviest materials.

10 Gauge construction throughout, with interlaced understructure.

Easy release, locking pins for tailgate, top and bottom.

Bolt on Sub frame, hoist and body, for ease of installation, transfer or replacement.

LED lighting for visibility and less maintenance.

2.5" lower bed height than previous models



HD-512 scissor hoist,  
5" bore x 16" stroke



Available in 304 *Stainless Steel*  
construction, with stainless  
interlaced understructure.

Stainless steel hinges  
w/ stainless pins.



# DUMP BODY - DROP SIDE SERIES

## SPECIFICATIONS

## 2017 SERIES

Length	Model	Sides	Cab to axle (CA)	Inside Dimensions (L x W x H)	Body Width	Cubic Yards (level, + 6", + 6")	Hoist capacity	Dump Angle	Weight (lbs.)
9' - 3"	DEDH09396 DEDHS09396	13" Hinged	60" CA GM, FORD, RAM (up to 19,500 GVW)	111" x 86" x 13"	96"	2.6, 3.8, 5.1	8 ton Class 20	50	1445

**Shipped fully assembled on hoist, sub frame and painted!**

## STANDARD FEATURES

**All models are bolt on installation.**

**Two Year Limited Warranty**

### GENERAL

- \* 10 gauge body & bed.
- \* Dirt shedding , sloped design at side plate and tailgate top
- \* Double panel, Stainless steel 12 gauge side plates (*both models*)
- \* Dual pin latches per side, for safety and simplicity
- \* Full depth 3/16" rear corner pillars incorporate recessed lighting, keyhole banjo eyes and lower tailgate pin receiver.
- \* All lighting is LED rubber mounted and NTEA and Federal compliant.
- \* 2 1/2" shorter deck height (*9' only*)
- \* Mounting height of 9.5" *chassis to floor* (*9' only*)
- \* 8" board extension pockets
- \* Self aligning rear latch release for the top gate pins
- \* Integrated tarp hooks
- \* DuPont™ Imron® Elite black oven cured paint w/ epoxy primer

### TAILGATE

- \* Formed 10 gauge inner, outer and end panels.
- \* 1" hardened pins, (1" Stainless) with plasma cut latch receiving lock fingers.
- \* Adjustable 1/4" chain for spreading aggregate material & holding gate in down position.

### FLOOR & UNDERSTRUCTURE

- \* 3" structural channel interlaced cross members (painted model)
- \* 3/16" formed 7" long sills
- \* 3" stainless tubing, interlaced cross members (*SS body*)
- \* Two piece 10 gauge floor
- \* Bolt on sub frame and scissor hoist.
- \* Greasable *Bronze* bearings for underbody release mechanisms (adjustable front & rear)

### CAB SHIELD

- \* 12" (1/4 cab) 10GA (12GA SS) cab protector
- \* Slotted dual windows
- \* overhang, standard.
- \* 10 gauge side panels with pre punched tarp mounting provisions.
- \* Straight overhang for ease of accessory installs

### OPTIONS

- \* *Stainless body construction*
- \* Tarp assembly, manual
- \* Coal chute, installed, painted or stainless
- \* Backup, running or strobe lights in apron (*painted model*)

Dual action pump, shipped installed



One handed, self aligning, locking latch w/ integrated spring retention



**DownEaster** 

120 Old Lisbon RD. - Topsham, ME 04086

(207) 729-5101 - Fax (207) 729-8782

[www.downeastermfg.com](http://www.downeastermfg.com)

**NTEA**  
THE ASSOCIATION FOR THE WORK TRUCK INDUSTRY™

**Distributed by:**



Specifications subject to change without notice