



BUILT TOUGH, BUILT TO LAST, Since 1979

DELD SERIES LANDSCAPER



Class 20 & 40, hoists
available

Shown w/ options

Shipped assembled on hoist & Sub Frame

LANDSCAPE BODY SPECIFICATIONS - SCISSOR HOIST DEL SERIES

Length	Model	Cab to axle (CA)	Mounting length	Inside Dim. (I.D.) (L x W x H)	Overhang	Body Width	Cubic Yards	Hoist capacity	Dump Angle	Weight (lbs.) *
9'-6"	DELD09696	60"	106"-108"	114" x 92" x 48"	8"	96"	10.8	8 ton class 20 *	50	1750
12'	DELD1296	84" - 96"	130"-132"	143.5" x 92" x 48"	13.5"		13.6	9 ton class 40		2000

*Class 40 hoist optional

*Weight is body only, no hoist

STANDARD FEATURES

FIVE Year Limited Warranty

GENERAL

- * 5" x 6.7# Channel long sills
- * 3" x 4.1# Channel cross members
- * 10GA floor, 2 pc
- * 12GA side plates & bulkhead
- * 52" Curb side door, *standard*
- * Structural tubing corner posts
- * 3/16" thick rear cross member/apron with tail and reverse light knockouts
- * 3/8" D rings at each inside corner
- * All lighting is LED rubber mounted and NTEA and Federal compliant.
- * Class 20 & 40 (single cylinder) hoists available
- * Mounted & painted Sub frame for ease of installation
- * Mounting hardware and brackets provided
- * Epoxy primer with Phosphate prewash
- * Paint, oven cured, with epoxy primer

TAILGATE

- * Full Height Barn doors, standard, with cam latch and lockable hasp
- * Secondary spring pin latch on Right side door.
- * Doors open 270 degrees
- * **Optional** two way spreader / dump gate, 20" high with upper solid barn doors.
- * Coal chute(s), installed on center two way gate

CAB SHIELD

- * **Bolt on, multi height position**, 12GA cab protector , 42" overhang
- * 12" overhang style for tilting passenger cab(Isuzu)
- Integrated tie down slots for up to 3, 6cu ft wheel barrows

OPTIONS

- * Pull out 2 step ladder on curb side access door
- * Tarp assembly, manual
- * 1/4 (12") & 42" overhang cab shields
- * **Subframe / hoist delete (order DEL)**
- * Hydraulic pump delete (for PTO)



Distributed by: