



DEDH DROP-SIDE DUMP BODIES

— BUILT TOUGH. BUILT TO LAST. —



BUILT FOR PERFORMANCE

- The DownEaster DEDH Dump Body is designed for professionals who demand lasting performance. Built from high-strength materials and precision-engineered for efficiency, it delivers dependable results on every job.
- From hauling aggregates to handling heavy loads, the DEDH Series provides rugged reliability and smooth operation day after day.
- Crafted for strength, durability, and ease of use.
- A proven performer in the field, the DEDH combines heavy-duty construction with a clean, efficient design built to keep your operation moving.
- Built tough, built right, and built to work.
- Three-year limited warranty.



207-729-5101 | 10 Recycle Dr, Topsham, Maine 04086

www.downeastermfg.com

DROP SIDE DUMP BODY SPECIFICATIONS - SCISSOR HOIST DEDH SERIES

Length	Model	Drop Sides	Cab to Axle (CA)	GVWR	Inside Dim. (I.D.) (L x W x H)	Mounting Length	Body Width	Cubic Yards	Hoist Capacity	Dump Angle	Weight (lbs.)
9'-3"	DEDH09396-HD DEDHS09396-HD	16"	60" CA	16.5k-19.5K	111" x 86" x 16"	106" to 108"	96"	4-7 yard	8 ton	50	1800
11'-3"	DEDH11396-HD DEDHS11396-HD	16"	84" CA	16.5k-19.5K	135" x 86" x 16"	130" to 132"	96"	4-7 yard	9.5 ton	48	2150

STANDARD FEATURES

Three Year Limited Warranty

GENERAL

- 10-gauge construction throughout for superior strength and longevity
- Sloped side plates and tailgate top designed to shed dirt and debris efficiently
- Double-panel side plates provide a combined thickness of over 1/4"
- Full-depth 3/16" rear corner pillars feature integrated recessed lighting
- Keyhole banjo eyes and lower tailgate pin receiver
- All lighting is LED rubber-mounted and fully compliant with NTEA and federal standards
- 2 -1/2" reduced deck height for lower center of gravity (*9' only*)
- Mounting height of 9.5" **chassis to floor** (*9' only*)
- Self-aligning rear latch release for the top gate pins
- Integrated tarp hooks
- Includes all mounting hardware and brackets
- Acid-etched, epoxy primed, and oven-baked finish for corrosion resistance

FLOOR & UNDERSTRUCTURE

- 4" x 5.7 lb. channel long sills and 3" channel crossmembers (*9' only*)
- 6" x 8.2 lb. channel long sills (*11' only*)
- 3/16" stainless formed 7" long sills (*SS body*)
- 3" stainless tubing interlaced crossmembers (*SS body*)
- Two-piece 10-gauge floor with 45 degree sloped corners
- Greaseable bronze bearings for underbody release mechanisms

TAILGATE

- Formed 10-gauge inner, outer, and end panels
- Stainless steel latch assemblies
- 1" hardened pins with latch receiving lock fingers
- Adjustable 1/4" chain for spreading aggregate material & holding gate in down position
- 27" height

CAB SHIELD

- Adjustable bolt-on, 10GA (12GA SS) cab protector, for ease of install & future optional custom overhang
- 18" overhang cab shield
- Pre-punched tarp mounting provisions
- Slotted dual windows

OPTIONS

- **Stainless body construction**
- 30" or 40" cab shield
- Manual or spring-loaded tarp assembly
- 3/16" flooring upgrade
- 12" spreader apron, bolt-on or weld-on
- Coal chute(s), installed (painted or stainless)
- 10" board extension pockets
- Backup, running, or strobe lights in apron
- Subframe/hoist/pump delete options

Dual-action Pump, Installed



Stainless Steel Locking Latch w/
Integrated Spring Retention



Champion Hoist, Installed



Find a dealer near you at
www.downeastermfg.com

