

DELD LANDSCAPE BODIES

BUILT TOUGH, BUILT TO LAST. =



STRENGTH YOU CAN DEPEND ON

- Designed with contractors in mind, the DownEaster DELD
 Landscape Body delivers unmatched durability and functionality on every job site.
- From hauling to spreading, the DownEaster DELD Landscape Body is built to handle the toughest workloads with ease.
- Crafted from premium materials and engineered for everyday performance.
- Dependable performance, season after season.
- Built for landscapers, by professionals who understand the demands of the trade.
- Three-year limited warranty.



warranty.

207-729-5101 | 10 Recycle Dr, Topsham, Maine 04086

www.downeastermfg.com

LANDSCAPE BODY SPECIFICATIONS - SCISSOR HOIST DELD SERIES

Length	Model	Fixed Sides	Cab to Axle (CA)	Overhang	Inside Dim. (I.D.) (L x W x H)	Mounting Length	Body Width	Cubic Yards	Hoist Capacity	Dump Angle	Weight (lbs.)
9'-6"	DELD09696	48"	60" CA	8"	114" x 92" x 48"	106"- 108"	96"	10.8	8 ton	50	1750
12'	DELD1296	48"	84"- 96" CA	13.5"	143.5" x 92" x 48"	130"- 132"	96"	13.6	9.5 ton	50	2000

STANDARD FEATURES

Three Year Limited Warranty

GENERAL

- 5" x 6.7 lb. channel long sills
- 3" x 4.1 lb. channel crossmembers
- 10-gauge two-piece steel floor
- 12-gauge steel side plates and bulkhead
- 54" curb side door
- · Structural tubing rear corner posts
- 3/16" rear crossmember/apron with reverse and tail light knockouts
- 3/8" D-rings located at each inside corner
- All lighting is LED rubber-mounted and fully compliant with NTEA and federal standards
- Available with Class 20 and Class 40 single-cylinder hoists
- Mounted and painted subframe for ease of installation
- Includes all mounting hardware and brackets
- · Acid-etched, epoxy primed, and oven-baked finish for corrosion resistance
- · 3-year limited warranty



TAILGATE

- · Full height barn doors with cam latch and lockable hasp
- · Secondary spring pin last on right side door
- · Doors open 270 degrees

CAB SHIELD

- Adjustable bolt-on, 12-gauge cab protector, for ease of install and future optional custom overhang
- 12" or 42" overhang cab shield
- · Integrated tie-down slots for up to three 6cu ft. wheel barrows
- Pre-punched tarp mounting provisions

OPTIONS

- 12" or 42" cab shield
- · Two-way 20" dump gate with upper barn doors
- · Manual or spring-loaded tarp assembly
- Coal chute(s), installed (painted)
- Pull-out 2 step ladder on curb side access door
- · Subframe/hoist/pump delete options

Dual-action Pump, Installed



Two-way 20" Dump Gate w/ Upper Barn Doors



Champion Hoist, Installed







