## **About Us**

Welcome to Downeaster Manufacturing! Based in the heart of Maine, we're a family run business that has proudly served the truck equipment industry for over 40 years.

Specializing in truck bodies, sand spreaders, and roll-off truck systems, we are committed to delivering products that reflect exceptional craftsmanship and durability.

Our dedication to quality ensures that our solutions meet the needs of the hardworking individuals who rely on them every day.











## **Sand Spreaders**

## **Contact Us**

- 207-751-3393
- www.downeastermfg.com
- jason@downeastermfg.com
- 10 Recycle Dr Topsham, ME 04086





## 24" Hydraulic Spreaders

#### 5.0-15 Yard



<u>Heigh</u>	<u>.</u> 9'	10'	11'	12'	13'	14'	15'	16'
48"	5.1	5.6	6.2	6.8	7.3	7.9	8.4	9.2
54"	6.2	7.0	7.6	8.4	9.0	9.7	10.3	11.2
60"	7.4	8.3	9.0	9.9	10.7	11.6	12.2	13.2
66"	8.6	9.5	10.3	11.5	12.3	13.5	14.2	15.2

Capacity (Cubic Yards)

#### **Standard Features**

- 3/16" stainless steel conveyor bed
- 6:1 spur gear
- Hinged & sloped removable top screens
- Remote grease fittings
- 667 pintle chain w/ 9500 lb tensile strength
- Adjustable feed gate, via screw jack
- Rear tension adjustment assembly
- 4 corner tie down points
- Vertical gussets every 24"

# 14" Gas & Electric Spreaders

#### 0.3-1.4 Yard

Available in 2', 4',
6', 7' and 8'

#### 1.5-2.5 Yard

• Available in 6', 7 8' and 9'

#### 3.0-8.0 Yard

Available in 8', 9',
 10' and 12'

#### **Standard Features**

- In cab, rocker switch control box
- Hinged / removable top screens
- Enclosed / hinged motor platform w/ venting
- 1-1/8" diameter conveyor shafts w/ 6T cast sprockets
- 662 Pintle chain w/ 8500 Ib tensile strength
- Greaseable, self aligning, drive bearings throughout
- Recessed lifting hook
- 4 corner tie down points
- Enclosed chute w/ 2 internal adjustable baffles & 3 external adjustable spreading deflectors

#### **Options**

- Direct, hydraulic drive
- ¾ HP electric single drive motor
- Dual electric drive motors
- Wireless remote control
- Extended chute 12"
- Inverted V
- Flip chute
- Front & rear spill sheilds
- 24 group marine battery
- Poly spinner disc

### **Tailgate Spreaders**



#### **Standard Features**

- Works with 96" wide dump bodies
- Rugged 6" auger with 3/8" flighting
- Handles bulk salt or a 50/50 sand/salt mix
- 18" poly spinner can cast material up to 25'
- High quality 304 stainless steel construction
- Available in electric or hydraulic

## **Drop Spreaders**





#### Standard Features

- 1/₃ cubic yard (.033)
- Hydraulic drive, 9.7 cubic inch motor (5 to 8 GPM)
- 44" W x 36" H x 21" D
- Adjustable drop / spread rate adjustments
- Electric drive, 3/4 HP, stainless motor
- 5/16" rod top screen
- Integrated lifting hooks
- Fits holder tractors
- LED lighting
- Self aligning bearings
- Mixing tine for material agitation

