

XD DUMP BODIES

BUILT TOUGH. BUILT TO LAST. —



BUILT FOR THE LONG HAUL

- Designed for professionals who demand more from their equipment, the DownEaster XD Dump Body delivers superior durability and maximum payload efficiency.
- From construction sites to landscaping jobs, the XD Series is built to take on your toughest loads and keep performing season after season.
- Precision-welded, corrosion-resistant, and made for serious work.
- Heavy-duty steel construction meets DownEaster craftsmanship for a dump body that works as hard as you do.
- Three-year limited warranty.





207-729-5101 | 10 Recycle Dr, Topsham, Maine 04086

www.downeastermfg.com

DUMP BODY SPECIFICATIONS - MEDIUM DUTY XD SERIES

Length	Model	Fixed Sides	Cab to Axle (CA)	GVWR	Inside Dim. (I.D.) (L x W x H)	Mounting Length	Body Width	Cubic Yards	Hoist Capacity	Dump Angle	Weight (lbs.)
10'	DED1096 XD DEDS1096 XD	30"	96" CA	26K-33K	119.5" x 86" x 30"	118"	96"	6.5 - 8.7	17-23 Ton	50	3820

STANDARD FEATURES

Three Year Limited Warranty

GENERAL

- ATSM 572 Grade 50 high-tensile steel (65 ksi) used throughout the body interior
- 10-gauge Grade 50 front panel with integrated stiffener
- Double-panel side plates exceeding 5/16" total thickness
- 10-gauge outer panels for durability and tailgate retention
- Full-depth 3/16" rear corner pillars featuring recessed lighting, keyhole banjo eyes, and lower tailgate pin receiver
- · Dirt-shedding, sloped design on side plates and tailgate top
- · Class 70 dual cylinder hoist
- All lighting is LED rubber-mounted and fully compliant with NTEA and federal standards
- Mounted and painted subframe for ease of installation
- · Includes all mounting hardware and brackets
- Acid-etched, epoxy primed, and oven-baked finish for corrosion resistance
- · 3-year limited warranty

FLOOR & UNDERSTRUCTURE

- 3/16" Grade 50 steel floor with radius corners and single weld seam
- 10" x 3/16" formed long sills with interlaced crossmembers
- 4" x 5.7 lb. channel crossmembers, including 3/16" formed crossmembers over the hoist
- Greaseable bronze bearings for underbody release mechanisms
- Standard front-handle tailgate release
- Dual safety props for added security

TAILGATE

- Formed 3/16" Grade 50 inner panel with 10-gauge outer and end panels
- 1-1/4" lower lock pins with forged latch lock fingers
- Adjustable 5/16" chain for spreading aggregate material & holding gate in down position
- 1.50" diameter 4140 steel hinge pins

CAB SHIELD

- Adjustable bolt-on, 10-gauge (12-gauge SS) cab protector, for ease of install & future optional custom overhang
- Standard 24" (1/2 cab) overhang
- · Pre-punched tarp mounting provisions

OPTIONS

- · Stainless steel body construction
- · Manual or spring-loaded tarp assembly
- Coal chute(s), installed (painted or stainless)
- Air-powered tailgate lock release cylinder
- 10" board extension pockets
- Electric-over-hydraulic pump
- 12" spreader apron, bolt-on or weld-on
- · Secondary oval knockout in rear post for flashing or turn signal lights
- Up to three vertical braces per side for added strength
- · Pre-punched oval cutouts for side and front-facing flashing lights

Greaseable Latch Bearings



Optional Coal Chute & Apron



Class 70 Dual Cylinder Hoist







